




- NOTES:
0. ALL DRAWINGS ARE IN METRIC MEASUREMENTS
 1. ALL ENGINEERING PRACTICES SHALL BE APPLIED WITH REGARDS TO HOLE AND SHAFT TOLERANCES.
 2. WHERE SCREWS OR BOLTS ARE USED THE CLEARANCE HOLES SHALL BE APPROXIMATELY 5% TO 8% LARGER THAN THE MATCHING TAPPED HOLE.
 3. PREFERABLY ALL TAPPED HOLES AND MATCHING SCREWS AND/OR BOLTS TO BE METRIC FINE (MF)
 4. MATERIALS SPECIFIED ON THE DRAWINGS ARE INDICATIVE ONLY. THE BUILDER CAN MAKE HIS/HER OWN MATERIAL CHOICE.
 5. ALL CONNECTIONS/JOINTS WHICH HAVE STEAM PRESSURE APPLIED TO IT SHALL BE SILVER/HARD SOLDERED.
 6. COMPRESSION SPRINGS ARE DRAWN IN COMPRESSED STATE (CP), UNCOMPRESSED STATE IS APPROX 40% TO 60% LONGER THEN COMPRESSED STATE.
 7. WHERE PREFERRED SCREW OR RIVETED CONNECTIONS CAN BE OMITTED AND PARTS CAN BE BONDED TOGETHER BY USING EITHER HIGH STRENGTH GLUE, EPOXY RESIN, OR SOLDER.
 8. PARTS WHICH ARE DIRECTLY EXPOSED TO STEAM AND/OR WATER SHOULD BE CONSTRUCTED USING NON-FERROUS OR NON CORROSIVE MATERIAL SUCH AS BRASS, BRONZE, GUNMETAL, STAINLESS STEEL, COPPER OR MONEL.
 9. THE ORDER IN WHICH THE PARTS/COMPONENTS ARE MANUFACTURED AND THE MODEL IS ASSEMBLED IS ENTIRELY LEFT TO THE BUILDER/MODEL MAKER.
 10. A COLOUR SCHEME FOR THIS PROJECT IS ENTIRELY LEFT UP TO THE MODEL MAKER.
 11. THE MANNER IN WHICH THE PARTS/COMPONENTS ARE MANUFACTURED IS ENTIRELY LEFT UP TO THE BUILDER.
 12. USE LOCTITE, ON SCREW OR PRESS FIT CONNECTIONS OR SURFACES, WERE DEEMED NECESSARY TO PREVENT PARTS FROM LOOSENING.
 13. WASHERS AND/OR SPRINGWASHERS SHALL BE USED WHERE DEEMED NECESSARY.
 - XX. ERRORS AND/OR OMISSIONS MAY OCCUR IN THE DRAWINGS, DO NOT HESITATE TO CONTACT ME SO THAT THE ERRORS/OMISSIONS CAN BE RECTIFIED.


MATERIAL ABBREVIATIONS:

ALU = ALUMINIUM
HALU= HARD ALUMINIUM
BRS = BRASS
BRZ = BRONZE OR GUNMETAL (BRZ/GM)
CI = CAST IRON
CU = COPPER
GRA = GRAPHITE
MS = MILD STEEL/BRIGHT MILD STEEL
SS = SILVER STEEL OR STAINLESS STEEL
SPS = SPRING STEEL
PEEK= POLYETHER ETHER KETONE
SYN = SYNTHETIC MATERIAL SUCH AS VETON, NYLON, TEFLON OR RUBBER
IN GENERAL SYNTHETIC MATERIALS SOULD BE ABLE TO WITHSTAND THE HEAT AND PRESSURE(S) APPLIED TO THEM.

nnn/nnn MEANS THAT EITHER MATERIAL CAN BE USED

OTHER ABBREVIATIONS

DP = DEEP
DAA= DRILL AFTER ASSEMBLY
D&TAA= DRILL AND TAP AFTER ASSEMBLY
CF = CLOSE FIT (SIZE FOR SIZE)
PF = PRESS FIT
PFAA= PRESS FIT AFTER ASSEMBLY
PCD = PITCH CIRCLE DIAMETER
RM = REAM
HEX = HEXACON, 6SIDED
CP = COMPRESSED
KNL = KNURLED
CSK = COUNTERSINK
PL = PLACES
DWL= DOWEL
SPF= SPOTFACE
(T)HESOP=(TAPPED)HOLES EQUALLY SPACED ON PCD
(T)HESOC=(TAPPED)HOLES EQUALLY SPACED ON CIRCUMFERENCE
[SA-xxx]= SUB ASSEMBLY-xxx



THE OFF SET ANGLE OF THE ECCENTRIC IN RELATION TO THE CRANK AXIS TO BE EXPERIMENTALLY DETERMINED FOR THE SMOOTH RUNNING OF THE ENGINE AND SATISFACTION OF THE BUILDER

QTY.	PART NUMBER
1	09B-21-00-1-01-BEDPLATE
1	09B-21-00-1-02-CRANKSHAFT BEARING-A
1	09B-21-00-1-03-CRANKSHAFT BEARING-B
1	09B-21-00-1-04-CENTER DRIVE SHAFT BEARING-C
1	09B-21-00-1-05-LOWER BEARING-D1
1	09B-21-00-1-06-LOWER BEARING-D2
2	09B-21-00-1-07-CRUSHING ROLLERS BEARING
1	09B-21-00-1-08-CYLINDER+VALVE CHEST
1	09B-21-00-1-09-CYLINDER FRONT COVER
1	09B-21-00-1-10-CYLINDER REAR COVER
1	09B-21-00-1-11-VALVE CHEST COVER
1	09B-21-00-1-12-CROSSHEAD GUIDE
1	09B-21-00-1-13-DUMMY WATER PUMP
1	09B-21-00-1-14-CANE JUICE COLLECTOR TANK
1	09B-21-00-1-15-REGULATOR HOUSING
1	09B-21-00-1-16-REGULATOR VALVE
1	09B-21-00-1-17-LOADING TRAY
1	09B-21-00-1-18-DUMMY JUICE PUMP
1	09B-21-00-1-19-EXHAUST PIPE
1	09B-21-00-2-01-CRANKSHAFT+FLYWHEEL
1	09B-21-00-2-02-WATER PUMP ECCENTRIC
1	09B-21-00-2-03-WATER PUMP ECCENTRIC STRAP
1	09B-21-00-2-04-WATER PUMP PISTON
1	09B-21-00-2-05-SLIDE VALVE
1	09B-21-00-2-06-VALVE SPINDLE
1	09B-21-00-2-07-SLIDE VALVE ECCENTRIC
1	09B-21-00-2-08-SLIDE VALVE ECCENTRIC STRAP
1	09B-21-00-2-09-PISTON+ROD
1	09B-21-00-2-10-CON ROD
1	09B-21-00-2-11-ILDER SHAFT-1
1	09B-21-00-2-12-ILDER SHAFT-2
1	09B-21-00-2-13-ILDER SHAFT-3
1	09B-21-00-2-14-TOP MILL ROLLER
2	09B-21-00-2-15-LOWER MILL ROLLER
1	09B-21-00-2-16-IDLER MILL ROLLER
1	09B-21-00-2-17-DUMMY JUICE PUMP PISTON
1	09B-21-00-2-18-DUMMY JUICE PUMP CON-ROD
8	09B-21-00-M2.5 NUT
4	09B-21-00-M2.5x12 A-K CYL HEAD SCREW
8	09B-21-00-M2.5x4 A-K CYL HEAD SCREW
2	09B-21-00-M2.5x5 A-K C-SINK SCREW
19	09B-21-00-M2.5x6 A-K CYL HEAD SCREW
5	09B-21-00-M3 NUT
8	09B-21-00-M3x10 A-K CYL HEAD SCREW
41	09B-21-00-M3x6 A-K CYL HEAD SCREW
18	09B-21-00-M4 NUT
25	09B-21-00-M4x10 A-K CYL HEAD SCREW
14	09B-21-00-M4x16 A-K CYL HEAD SCREW
6	09B-21-00-M4x20 A-K CYL HEAD SCREW
8	09B-21-00-M4x6 A-K CYL HEAD SCREW
6	09B-21-00-M5x12 A-K CYL HEAD SCREW
8	09B-21-00-M5x8 A-K CYL HEAD SCREW
1	09B-21-00-M8 NUT

NOTES: THIS DESIGN IS BASED ON DRAWINGS PUBLISHED ON THE "MODELENGINEERINGWEBSITE" WEBSITE.

TITLE
A MODEL OF A SUGAR CANE MILL AS
MANUFACTURED BY MESSERS. ROBEY&CO

DRAWING CONTENTS
ISOMETRIC VIEWS, NOTES AND
BILL OF MATERIALS

PROJECT No 09B-21-00
JDW DRAUGHTING SERVICES
J.A.M. DE WAAL, 12 BRIGHTWELL STREET PAPAURA
2110, NEW ZEALAND. PHONE: 0064 09 2988815. MOB:
0211791000 E-MAIL: dewaal@xtra.co.nz.

PROJECTION
DATE JUNE 2019
SHEET: 02 OF 09
JDWDS
Copyright © J.A.M. DE WAAL PAPAURA NZ
MODEL SCALE: 1:10
DWG SCALE: 1:1 @A3 OR AS SHOWN
A3 No: 09B-21-00-SHT02

DRAWINGS ARE FOR PERSONAL USE ONLY NOT FOR COMMERCIAL PURPOSES